

## DATASHEET TRASSIR DuoStation AnyIP 16/24/32



**TRASSIR DuoStation** is a network video recorder for building CCTV systems.  
Up to 32 channels are available for record, playback and display.

### Rear panel:



1. AC 220V power input
2. USB 3.0 (Type-A)
3. Audio input/output
4. Network interface
5. D-SUB interface
6. HDMI interface

Specification:

Operating system	TRASSIR OS (based on Linux)
IP video input <sup>1</sup>	16/24/32-ch (any models <sup>2</sup> )
Video compression <sup>3</sup>	Up to 8MP (depending on camera model <sup>2</sup> )
Bitrate	Up to 512Mb/s
Video compression	H.265+, H.265, H.264, MPEG4 or MJPEG (depending on camera model <sup>2</sup> )
Network interfaces	2xEthernet 10/100/1000 Mb/s
USB interfaces	4xUSB 3.0 and 1xUSB 2.0
Maximum internal storage	Up to 4xHDD (3.5")
Video output <sup>4</sup>	1 D-SUB 1 HDMI
Maximum video output resolution	D-SUB: FullHD HDMI: 2K <sup>5</sup>
Dimensions, mm	185 x 232 x 185
Power supply	AC 220V (100W)
Power consumption	30W (without HDD)
Working temperature	10...30°C
Package size, mm	300 x 265 x 337
Gross, kg	5.5

<sup>1</sup> Depending on NVR model.  
<sup>2</sup> You can find list of per-integrated cameras on [www.trassir.com](http://www.trassir.com).  
<sup>3</sup> Enable hardware acceleration in TRASSIR to view the video in the resolution of 8 megapixels.  
<sup>4</sup> The NVR can be connected to two independent displays.  
<sup>5</sup> Supported when hardware acceleration is enabled.

Basic equipment:

- Network Video Recorder ..... 1 pcs
- Power cord ..... 1 pcs
- Datasheet for server ..... 1 pcs

Warranty service:

- Specify the information about the warranty on [www.trassir.com](http://www.trassir.com).

DATE OF PRODUCTION

KEY NUMBER

SERIAL NUMBER